

WEST[Help](#)[Logout](#)[Main Menu](#)[Search Form](#)[Result Set](#)[Show S Numbers](#)[Edit S Numbers](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#)[Title](#)[Citation](#)[Front](#)[Review](#)[Classification](#)[Date](#)[Reference](#)[Claims](#)[RIMC](#)

Document Number 68

Entry 68 of 179

File: JPAB

Aug 15, 1997

PUB-NO: JP409214484A

DOCUMENT-IDENTIFIER: JP 09214484 A

TITLE: LINE CONCENTRATOR FOR VOICE TELEPHONE SET AND COMMUNICATION METHOD FOR LAN

PUBN-DATE: August 15, 1997

INVENTOR-INFORMATION:

NAME

USUHA, SHINJI

KONISHI, TOMOKAZU

SEKINE, YOSHINORI

ASSIGNEE-INFORMATION:

NAME

OKI ELECTRIC IND CO LTD

COUNTRY

N/A

APPL-NO: JP08018999

APPL-DATE: February 5, 1996

INT-CL (IPC): H04L 12/02; H04L 12/28; H04M 3/00

ABSTRACT:

PROBLEM TO BE SOLVED: To contain a voice telephone set to a LAN

SOLUTION: In the case of making communication from a voice telephone set 5 to a voice telephone set 8 for example, information is exchanged between personal computers 2, 4 ancillary to them via a switch device 50 and a LANhub 20 and call control is conducted. LANhub 10, a Voice LAN data of the voice telephone sets 5, 8 are processed into packets into a data part of each MAC frame by TLAs 30, 40 and relays to LANSW Interfaces 30a, 40a. A frame having fluctuation absorption function is applied to the data part on the interfaces 30a, 40a. Based on the MAC address of the MAC frame, voice data processed as packets are given respectively to the telephone sets 8, 5 via the TLAs 40, 30.

COPYRIGHT: (C)1997,JPO

[Main Menu](#)[Search Form](#)[Result Set](#)[Show S Numbers](#)[Edit S Numbers](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#)[Title](#)[Citation](#)[Front](#)[Review](#)[Classification](#)[Date](#)[Reference](#)[Claims](#)[RIMC](#)[Help](#)[Logout](#)